

Blind - JIS B2220 - 1984 (KSB1503 - 1985) 10KG/CM2

STS		JIS B2220-1984(KSB1503-1985)			16KG/CM2	
BLIND MM						
size	outside dia.	thickness	bolt hole circle	bolt hole dia.	bolt hole	appro. weight
DN	D	b	K	d2	No.	kg
15	95	12	70	15	4	0.6
20	100	14	75	15	4	0.79
25	125	14	90	19	4	1.23
32	135	16	100	19	4	1.66
40	140	16	105	19	4	1.81
50	155	16	120	19	8	2.1
65	175	18	140	19	8	3.1
80	200	20	160	23	8	4.5
90	210	20	170	23	8	5
100	225	22	185	23	8	6.3
125	270	22	225	25	8	9.2
150	305	24	260	25	12	12.8
200	350	26	305	25	12	18.6
250	430	28	380	27	12	30.6
300	480	30	430	27	16	40.7
350	540	34	480	33	16	57.8
400	605	38	540	33	16	82.2
450	675	40	605	33	20	107.5
500	730	42	660	33	20	133.1
550	795	44	720	39	20	164.1
600	845	46	770	39	24	193.2
650	895	48	820	39	24	227.5
700	960	50	875	42	24	272.6
750	1020	52	935	42	24	321.9
800	1085	54	990	48	24	
850	1135	56	1040	48	24	
900	1165	58	1090	48	28	
1000	1320	62	1210	56	28	
1100	1420	66	1310	56	32	
1200	1530	70	1420	56	32	
1300	1615	74	1530	62	32	
1350	1700	76	1590	62	32	
1400	1755	78	1640	62	36	
1500	1965	80	1750	62	36	